

## Hydraulic power packs:

The System No-Dig pipebursters are all powered by modern state-of-the-art power packs. The units are all fitted with the following features:

- Separate hydraulic oil cooling system.
- Low flow / high pressure hydraulic oil pump system.
- Remote & stationary operational options.
- Low emission water cooled Kubota diesel engines.
- Easy access maintenance areas.
- Can operate between -40°C. and +60°C.
- Desert air-filter systems, optional!

### Power pack T45/T65:

Kubota diesel. 3 Cyl. 25 bhp. /3000 rpm.

Hydraulic resoir holds 100 litres.

1 variable displacement pump system.

Operational oil pressures level; 250 bars.

Remote and stationary emergency systems.

All System No-Dig power packs are built on a heavy duty steel frame and driven by water cooled Kubota diesel engines.

A separate hydraulic oil cooling system makes the equipment capable of operating under extreme temperature conditions from -40°C to +60°C. Special sound proof materials and various filters are used to comply with some of the most strictly emission regulations like the "U. S. Environmental Protection Agency", (EPA) and the "California Air Resources Board", (CARB).

The T65 and T175 power pack can easily be adjusted to operate both the T45 and T65 pipe burster rigs.

### Power pack T85/T175:

Kubota diesel. 4 Cyl. 68 bhp. /2600 rpm.

Hydraulic resoir holds 160 litres.

2 variable displacement pump system.

Operational oil pressures level; 250 bars.

Remote and stationary emergency systems.



Close-up

Power pack T85 / T175