



**Hydrostatic Pipeburster - model T45**

The T45 Pipeburster with its 40 tonnes static pull back power, is capable of replacing existing pipes from;  
Ø 40 mm. up to Ø 200 mm.

The model is the narrowest machine on the market. This makes the T45 a highly flexible, light-weight unit, which fits in between even the closest parallel installations.

T45 is remote controlled and mounted with a built-in emergency strike system for safety.

Technical specifications:	T45 Pipeburster	T45 Power pack
Length:	1.80 meter	1.50 meter
Width:	0.23 meter	0.95 meter
Height:	0.70 meter	0.98 meter
Weight:	450 kg	550 kg

The T45 Pipe burster operates with two sizes of solid steel rod systems; Ø 45 mm as standard and the smaller Ø 35 mm. system, which allows the machine to replace pipes as small as Ø 40 mm.

The recommendable maximum length of replacing an existing pipe is 150 meters.

All steel rods are threaded in both ends and handled by a fully automatic unit called; “ARD45”. The automatic rod device spins the rods on and off and thereby minimizes any manual work whilst handling the round rods.

Approximately 45 min. is used to replace 100 meters of existing pipe.

Recommended dimensions for the T45 Pipeburster excavation:

Length:	3.00 meter
Width:	0.60 meter
Depth:	0.13 meter “below centre line of existing pipe”

